



The better 3phase PowerTRIO

The better flexibility

Battery ready inverter. DC or AC coupled
Full power 100% unbalanced backup

The better security

Patented AFCI
Patented RCD (Residual Current Device)

The better installability

Plug & play connections
Integrated spirit level

The better connectivity

Embedded Wi-Fi, Ethernet and USB
Modbus TCP (Sunspec)

Go for the better



One size for all

from 4 kW to 10 kW

x2

switching frequency

<20 dB (A)

noise reduction

+40%

time saving
for commissioning



24 / 7

real time monitoring

Battery ready

100%



Semplice

plug & play

100%

Full power unbalanced backup

Patented

ARC fault detection

Small

High power density

+55%

CPU performance

Integrated

SG ready

Built-in

Ethernet and Wi-Fi

Setup

Anytime

Technical data and types

Inverter	FIM-HY-4.0-SE-A-3PH	FIM-HY-5.0-SE-A-3PH	FIM-HY-6.0-SE-A-3PH	FIM-HY-7.5-SE-A-3PH	FIM-HY-8.0-SE-A-3PH	FIM-HY-8.5-SE-A-3PH	FIM-HY-10.0-SE-A-3PH
Input side							
Absolute maximum DC voltage ($V_{max,abs}$)	1000 V						
Start-up DC voltage (V_{start})	200 V adj. 150...500 V	200 V adj. 170...500 V	200 V adj. 200...500 V	215 V adj. 215...500 V	215 V adj. 215...500 V	215 V adj. 215...500 V	215 V adj. 215...500 V
Operating DC voltage range ($V_{dcmin}...V_{dcmax}$)	0.7 x $V_{start}...825$ V (min 110 V)	0.7 x $V_{start}...825$ V (min 130 V)	0.7 x $V_{start}...825$ V (min 145 V)	0.7 x $V_{start}...975$ V (min 155 V)	0.7 x $V_{start}...975$ V (min 155 V)	0.7 x $V_{start}...975$ V (min 155 V)	0.7 x $V_{start}...975$ V (min 155 V)
Rated DC voltage (V_{der})	625 V						
Rated DC power (P_{dc})	4128 W	5176 W	6205 W	7732 W	8247 W	8763 W	10256 W
Suggested maximum DC power ¹⁾	6000 W	7500 W	9000 W	11250 W	12000 W	12750 W	12750 W
DC/AC ratio	Up to 150%, according to location						
Number of independent MPPT	1	2	2	2	2	2	2
Maximum DC power for each MPPT ($P_{MPPTmax}$)	5625 W ²⁾ Linear derating $800 \leq V_{MPPT} \leq 850$ V	3882 W Linear derating $800 \leq V_{MPPT} \leq 850$ V	4654 W Linear derating $800 \leq V_{MPPT} \leq 850$ V	5799 W Linear derating $850 \leq V_{MPPT} \leq 1000$ V	6186 W Linear derating $850 \leq V_{MPPT} \leq 1000$ V	6572 W Linear derating $850 \leq V_{MPPT} \leq 1000$ V	6572 W Linear derating $850 \leq V_{MPPT} \leq 1000$ V
DC voltage range of MPPT ($V_{MPPTmin}...V_{MPPTmax}$) at P_{acr}	265...800 V	170...800 V	200...800 V	250...850 V	265...850 V	285...850 V	330...850 V
Maximum DC current ($I_{dc,max}$) / for each MPPT ($I_{MPPT,max}$)	16 A	32A / 16 A - 16 A (MPPT1 - MPPT2)	32A / 16 A - 16 A (MPPT1 - MPPT2)	32A / 16 A - 16 A (MPPT1 - MPPT2)	32A / 16 A - 16 A (MPPT1 - MPPT2)	32A / 16 A - 16 A (MPPT1 - MPPT2)	32A / 16 A - 16 A (MPPT1 - MPPT2)
Maximum short circuit current per MPPT	20 A						
Number of DC inputs pairs for each	1 (MPPT1)	1 - 1 (MPPT1 - MPPT2)	1 - 1 (MPPT1 - MPPT2)	1 - 1 (MPPT1 - MPPT2)	1 - 1 (MPPT1 - MPPT2)	1 - 1 (MPPT1 - MPPT2)	1 - 1 (MPPT1 - MPPT2)
DC connection type	Quick fit PV connector ³⁾						
Input protection							
Reverse polarity protection	Yes, from limited current source						
Over voltage protection for each MPPT - varistor	Yes						
Photovoltaic array isolation control	According to local standard						
DC switch rating for each MPPT	25 A / 700 V - 12 A / 1000 V						
Battery input/output							
Operating DC voltage range ($U_{dmin}...U_{dM}$)	600...850 V	600...850 V	600...850 V	600...980 V	600...980 V	600...980 V	600...980 V
Nominal operating DC voltage range ($U_{dNmin}...U_{dNm}$)	620 V						
Nominal operating DC voltage (U_N)	605 ... 635						
Withstand voltage(U_M)	980 V						
PowerX Max. units	2						
Max operating current ⁴⁾	17 A						
Maximum charge power from DC side ⁵⁾	5625 W	7764 W	9308 W	10256 W	10256 W	10256 W	10256 W
Maximum discharge power	4000 W	5000 W	6000 W	7500 W	8000 W	8500 W	10000 W
AC Output							
AC Grid connection type	Three-phase						
Rated AC power ($P_{acr} @ \cos\phi=1$)	4000 W	5000 W	6000 W	7500 W	8000 W	8500 W	10000 W
Maximum AC output power ($P_{acmax} @ \cos\phi=1$)	4000 W	5000 W	6000 W	7500 W	8000 W	8500 W	10000 W
Maximum apparent power (S_{max})	4000 VA	5000 VA	6000 VA	7500 VA	8000 VA	8500 VA	10000 VA
Rated AC grid voltage (V_{acr})	380 / 400 V						
AC voltage range ⁶⁾	320 / 480 V						
Rated Output Current at Vac 400 V(I_{acr})	5.8 A	7.2 A	8.7 A	10.9 A	11.6 A	12.3 A	14.5 A
Maximum AC current ($I_{ac,max}$)	6.1 A	7.6 A	9.1 A	11.4 A	12.2 A	12.9 A	15.2 A
Contributory fault current	6.1 A	7.6 A	9.1 A	11.4 A	12.2 A	12.9 A	15.2 A
Rated frequency (f_r)	50 Hz / 60 Hz						
Frequency range ($f_{min}...f_{max}$) ⁷⁾	45...55 Hz / 55...65 Hz						
Nominal power factor and adj. range	> 0.995, adj. \pm 0.8 - 1 (over/under excited)						
Total current harmonic distortion	< 3 % dI $I_{ac,max}$						
AC connection type	Female panel connector						
Grid connected output protection							
Anti-islanding protection	According to local standard						
Maximum external AC overcurrent protection	10.0 A	10.0 A	10.0 A	16.0 A	16.0 A	16.0 A	20.0 A
Output overvoltage protection - varistor	4 (L1-PE, L2-PE, L3-PE, N-PE), TYPE II protection class ⁸⁾						
Efficiency							
Maximum efficiency	97.7 %	97.9 %	97.9 %	97.9 %	97.9 %	97.9 %	98.3 %
Euro efficiency	95.9 %	96.8 %	97.0 %	97.3 %	97.3 %	97.4 %	97.9 %
MPPT efficiency	99.9 %						
Backup mode⁹⁾							
Voltage waveform	S (sine)						
Dynamic output performance	1 (linear load), 2 (non-linear load)						
Maximum apparent 3-PHASE power (S_{max})	4000 VA	5000 VA	6000 VA	7500 VA	8000 VA	8500 VA	10000 VA
Maximum apparent 1-PHASE power (S_{max})	1333 VA	1667 VA	2000 VA	2500 VA	2667 VA	2833 VA	3333 VA
Rated AC grid Voltage (V_{acr})	380 / 400 V						
AC Voltage range	320 ... 480 V						
Maximum AC current ($I_{ac,max}$)	6.1 A	7.6 A	9.1 A	11.4 A	12.2 A	12.9 A	15.2 A
Rated output frequency (f_r)	50 Hz / 60 Hz						
Frequency range ($f_{min}...f_{max}$)	45...55 Hz / 55...65 Hz						

Technical data and types

Inverter	FIM-HY-4.0-SE-A-3PH	FIM-HY-5.0-SE-A-3PH	FIM-HY-6.0-SE-A-3PH	FIM-HY-7.5-SE-A-3PH	FIM-HY-8.0-SE-A-3PH	FIM-HY-8.5-SE-A-3PH	FIM-HY-10.0-SE-A-3PH
Embedded communication							
Embedded physical interface	Wi-Fi ¹⁰⁾ , Ethernet, RS-485						
Embedded communication protocols	Modbus TCP (SunSpec)						
Datalogger data retention	30 days						
Remote monitoring	Energy Viewer (mobile APP), Energy Viewer Web, Plant Portfolio Manager						
Local monitoring	Energy Viewer (mobile APP) / Internal web server (WEB UI)						
Commissioning (Energy policy included)	Internal web server (Web UI)						
Environmental							
Ambient temperature range	-25...+60°C with derating above 50°C	-25...+60°C with derating above 50°C	-25...+60°C with derating above 45°C	-25...+60°C with derating above 45°C	-25...+60°C with derating above 45°C	-25...+60°C with derating above 45°C	-25...+60°C with derating above 40°C
Wet locations	Yes						
Relative humidity	4...100 % condensing						
Acoustic noise emission level (at rated DC voltage V_{DC})	< 40 dBA @ 1 m						
Acoustic noise emission level (worst case)	< 50 dBA @ 1 m						
Maximum operating altitude	3000 m (9842 ft) with derating above 2000 m (6561 ft)						
Ambient storage/transport temperature	-40 °C...+85 °C						
Humidity storage/transport	4 % ÷ 100 %						
Environmental classification	4K6 (IEC 62477-1:2022) /4K26 (IEC 60721-3-4:2019)						
Physical							
Environmental protection rating	IP65						
Cooling	Natural						
Dimension (H x W x D)	373 mm x 518 mm x 183 mm						
Weight	18 kg						
Mounting system	Wall bracket						
Safety							
Isolation level	Transformerless						
Overvoltage category according IEC 62109-1	OVC III (AC Port), OVCI (PV port and Battery port)						
Marking	CE, RCM						
Safety and EMC standards	IEC/EN 62109-1, IEC/EN 62109-2, IEC 62477-1, EN 61000-6-2, EN 61000-6-3, EN 61000-3-2, EN 61000-3-3, EN 61000-3-11, EN61000-3-12						
Grid standards (check your sales channel for availability) ¹¹⁾	CEI 0-16 ,CEI 0-21, DIN V VDE V 0126-1-1, VDE-AR-N 4105, G83/2, G59/3, G98-1, G99-1, RD 413, ITC-BT-40, AS/NZS 4777.2, C10/11, IEC 61727, IEC 62116						
Other features							
Load manager	Yes, with integrated relay						
AC backup, off grid	Yes						
Battery charge from AC	Yes, it can be enabled						
AC-coupled mode	Yes, settable during commissioning						

1) Value subject to derating; refer to the product documentation for further details.

2) Extra power available in conjunction with Battery ESS

3) Refer to the document "String inverter – Product Manual appendix" available at www.fimer.com/solarinverters to know the brand and the model of the quick fit connector

4) The maximum operating current applies to both the charging and discharging cases

5) Also limited by the capability of the installed Battery ESS

6) The AC voltage range may vary depending on specific country grid standards

7) The Frequency range may vary depending on specific country grid standards

8) As per test defined in EN/IEC 61643-11

9) PowerBOX required

10) As per IEEE 802.11 b/g/n standard


11) Further grid standards will be added, please refer to FIMER's Solar page for further details

Remarks:


- Designed and manufactured in Italy

- Features not specifically listed in the present data sheet are not included in the product

PowerTRIO: provides protection against blackouts



PowerTRIO: Multi-inverter installation





For more information
please contact
your local FIMER
representative or visit:

fimer.com

Preliminary data. We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. FIMER does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of FIMER.
Copyright© 2025 FIMER.
All rights reserved.

