

The better battery

PowerX

The better modularity

5.0 up to 15.0 kWh per battery system
Up to 2 battery systems, 30 kWh capacity

The better security

LFP chemistry in unibody design
Peace of mind installation

The better installability

Tool-free click-and-connect system
Pre-assembled plug & play cable for inverter connection

The better flexibility

Upgradable capacity during lifetime
Operating voltage from 350 up to 980V

Technical data and types

Battery system (Genius box + battery modules)	PowerX-5kWh	PowerX-10kWh	PowerX-15kWh
Battery system composition:			
- Bidirectional DC/DC Unit (Genius box)	PowerX-5kW	PowerX-5kW	PowerX-5kW
- Energy Storage Module (Battery module x q.ty)	PowerX-5kWh-BATT x 1	PowerX-5kWh-BATT x 2	PowerX-5kWh-BATT x 3
System data			
Cell chemistry	Lithium-iron phosphate (LiFePO4)		
Battery module	PowerX - 5kWh		
Battery module energy	5 kWh		
Number of battery modules	1	2	3
Battery usable energy ¹⁾	5 kWh	10 kWh	15 kWh
Max. output power	2.5 kW	5 kW	5 kW
Peak output power	3.5 kW, 10 s	7 kW, 10 s	7 kW, 10 s
DC Nominal voltage (single-phase system)	450 V		
DC Operating voltage range (single-phase system)	350 ... 560 V		
DC Nominal voltage (three-phase system)	600 V		
DC Operating voltage range (three-phase system)	600 ... 980 V		
Communication			
Display	LED indicator, SOC status indicator		
Communication ²⁾	RS485/CAN		
Environmental			
Environmental protection rating	IP66		
Operative ambient temperature ³⁾	-20 °C to +55 °C (-4 °F to +131 °F)		
Max. operating altitude ⁴⁾	4,000 m (13,123 ft.) (Derating above 2,000 m)		
Environment ⁵⁾	Outdoor (Please refer to the user manual for installation condition)		
Relative humidity	5%-95%		
Cooling	Natural convection		
Noise emission	< 29 dB		
General Specification			
Dimensions (W x D x H)	670 mm x 150 mm x 650 mm	670 mm x 150 mm x 1010 mm	670 mm x 150 mm x 1370 mm
Weight (Floor stand toolkit included)	63.8 kg (140.7lb)	113.8 kg (250.9lb)	163.8 kg (361.1lb)
Power module dimension (W x D x H)	670 mm x 150 mm x 240 mm		
Power module weight	12 kg		
Battery module dimensions (W x D x H)	670 mm x 150 mm x 360 mm		
Battery module weight ⁶⁾	50 kg		
Installation	Floor stand (standard), Wall mounting (optional) ⁷⁾		
Scalability	Max. 2 systems in parallel operation		
Compatible inverters	PowerUNO and PowerTRIO inverter families		
Standards Compliance ⁸⁾			
Marking	CE, RoHS, UKCA		
Certificates	IEC 62619, EN/IEC 62477, RoHS compliant, VDE2510-50, UN38.3		
EMC	EN 55011, EN/IEC 61000, EN/IEC 62920, CISPR11		


- 1) Test conditions: 100% depth of discharge (DoD), 0.2C rate charge & discharge at 25°C, at the beginning of life.
- 2) CAN is used only for parallel communication.
- 3) Refer to battery warranty letter for conditional application.
- 4) The output power may be affected by altitude. Please refer to the output derating curve for details.
- 5) Improper storage system installation may compromise product warranty and operation safety. Please follow the user manual during the installation, use, and

maintenance of the storage system.

- 6) The weight of the battery modules varies with products, with a tolerance of ±3%.
- 7) Dedicated installation kit required, to be purchased upon request.
- 8) Other standards available on request.

Remarks:

- Features not specifically listed in the present data sheet are not included in the product



12 kg
power module weight

+40 %
time saving
for commissioning

5 kW
charger power


module Tool-free
click-and-connect

Easy and safe
transportation and
installation

LiFePO4
Lithium iron phosphate

The better configurations



For more information please contact your local FIMER representative or visit:

fimer.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. FIMER does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of FIMER. Copyright© 2024 FIMER. All rights reserved.

